Tabbin Institute for Metallurgical Studies

Energy and Environment Research Center

E2RC

ISO 9001 -2008

Report on

Exhaust Stack Emissions Measurement from Cement Mill No. (9) Factor (2) Tourah Cement Company

Aqua Misr Company

November, 2014

Team Work

Prof. Dr.\ Tarek Mahmoud Samy

TIMS Director

Chem. \ Samier Hammad

General Manager of Central Lab.

Chem. \ Ragab Abdel Khalik

Head of Air Pollution Lab.



Introduction

According to the contract between Aqua Misr Co. and Energy and Environment Research Center / Tabbin Institute for Metallurgical Studies (TIMS) to execute Exhaust Stack emissions Measurement from the bag filter of cement Mill No.(9) factor (2) at Tourah Cement Company, TIMS team work had conducted these measurement in November, 2014.

- ⇒ Measurements
- The following parameters were measured from stacks of Cement Mill No. 9
 - 1. Concentration of dust emissions form stacks.
- 2. Concentration of combustion gases (Temp. O2) from stacks.

⇒ The Use Equipment

Exhaust stacks emissions for bag filter of Cement Mill No. 9
 Universal Stack sampler. USA

Sampling method : Isokinetic measurement

EPA method No. 1,2 velocity & flow rate

EPA method No. 5 dust emission

2 .Combustion gas analyzer Lancôm- III U.S.A





Table (1) Exhaust Stack Emission

Company Name

: Tourah Cement Company

Measurements date

: 22/11 /2014

Site Name

: Stack of Cement Mill No. (9) - Factor 2

Parameter	Unit	Out let	Maximum permissible limits according to law 4/1994 for Environment protection and its amendments by law No.9/2009 and its executive regulation issued in 1995 and its amendments issued no. 1095/2011 & 710/2012
Stack Temperature	°C	65	
Barometer P	mbar	1009	
Static Pressure	mmH ₂ O	-24	
Dynamic P. (Avg.)	mmH ₂ O	9.6	
Velocity	m/s	13.55	
H ₂ O	%	0.5	
O ₂	%	20.4	
Stack Flow Rate	m³/h	15833	
Dust concentration	mg/m³	9.4	50



